



SIGNWIRE SPEC 983840



14 AWG GTO-15 HI-TEMP MINI SUPERFLEX 15,000 VOLTS -105°C



UL & CSA LISTED GTO-15 FT2 RoHS COMPLIANT – GRAY

1.0 SCOPE

1.1 This specification covers FLEXIBLE miniature diameter neon sign gas tube oil burner ignition cable suitable for indoor and outdoor use for 15,000 volt service. Construction consists of stranded bare copper insulated with a SUNLIGHT RESISTANT Dielectric. Our TUF-HIDE® Mini Superflex construction is Specially DESIGNED FOR INSTALLATION IN METAL CONDUIT.

1.2 UV and Ozone Resistant

1.3 Open Circuit Voltage:

15 KVAC

1.4 Breakdown Voltage:

Exceeds 50,000 Volts

1.5 Dielectric Strength in MLS:

650V Per Mil

1.6 Temperature Rating:

-29°C +105°C

1.7 Fire & Flame Retardancy:

Cable Complies with VW-1

UL 1581, Section 1080, Flame Test

1.8 UL TW Oil Resistant:

1.9 *Sunlight Resistant

1.10 Easy Stripping

1.11 Cable Complies with UL Standard 814 - CSA C22.2 No. 127 for Gas Tube Sign and Ignition Cable

2.0 CONSTRUCTION

SIZE AWG	STRANDING	INTEGRAL W (MILS)	NOMINAL OVERALL DIAMETER	VOLTAGE RATING
14	19/.0147	98	.265"	15000V

2.2 Conductor:

Stranded bare copper conforming to UL Standard 814 – CSA C22.2 No. 127.

2.3 Insulation:

High dielectric strength single extrusion. Color Gray. Special colors can be supplied on request.

2.5 Surface Print:

"TUF-HIDE® HI-TEMP MINI SUPERFLEX 983840 14 AWG E135239 (UL) GTO-15 15000V 105C - CSA GTO-15 15000V 105C SUN RES FT2 - ROHS COMPLIANT"

2.6 Tests:

Physical and electrical tests in accordance with Underwriters Laboratories Standard No. 814 – CSA C22.2 No. 127.

2.7 Nominal Weight:

37 lbs/1000 Feet

2.8 Packaging:

250 ft. Cable Caddy dispensing box - Or special lengths can be Supplied on request

For further information on this specification: Call 1-800-327-2443 or Fax: 855-724-4365 or E-Mail: roxtobia@paigeelectric.com

*UL does not recognize any GTO cable as sunlight resistant.